

T15



hansaequipment.com.au

 **HANSA**
PRECISION EQUIPMENT

T15

Features and Benefits



BUILT FOR DURABILITY

Manufactured from 304 stainless steel, the T15 is built for durability. A grit blasted and 2 pack painted chassis ensures longevity and that return on investment of the T15 outperforms expectations.



BUILT FOR COMFORT

The T15 is built for comfort and ease of use, with hydraulic drawbar suspension for the best ride possible as standard and the option of an automatic door eliminating any need to get out to adjust settings meaning a long days spreading becomes a pleasure.



PERFORMANCE AND RELIABILITY

The reliable design of the Southern Spreaders 760 chain conveyor feeds the spinners to produce a positive and consistent product feed of all materials in all conditions and terrain.



ISOBUS

Simply Plug and play, the Hansa ISOBUS control system is compatible with all ISOBUS compliant terminals and is variable rate ready as standard. This allows the operator to move the spreader from one machine to another with ease and no setup changes.



Inclusions & Options

		Inclusions ●	Optional ○
TYRES	Alliance 331 600/60 R30.5 floatation tyre	<input type="radio"/>	<input type="radio"/>
	Harvest 600/65 R28 tractor tyre	<input checked="" type="radio"/>	<input type="radio"/>
	Michelin VF CFO+ 520/80 R26 tractor tyre	<input type="radio"/>	<input type="radio"/>
	Michelin CARGOXBIB 650/60 R30.5 floatation tyre	<input type="radio"/>	<input type="radio"/>
	Michelin MACHXBIB 600/70 R28 tractor tyre	<input type="radio"/>	<input type="radio"/>
TARP	900 gsm rollover tarp	<input type="radio"/>	<input type="radio"/>
LOAD CELLS	When selected with load ISOBUS rate controller auto dynamic calibration is enabled	<input type="radio"/>	<input type="radio"/>
RATE CONTROLLER	ISOBUS (auto rate calibration) Hansa H7 controller (7" Touch screen)	<input type="radio"/>	<input type="radio"/>
SECTION CONTROL	Twin conveyor for headland and section control (available with H7 & ISOBUS rate controllers)	<input type="radio"/>	<input type="radio"/>
AXLE	Tandem 150mm Square Axle Beam, with Rear Steerable Axle (track options of 2,500mm & 3,000mm)	<input checked="" type="radio"/>	<input type="radio"/>
BRAKES	Hydraulic	<input type="radio"/>	<input type="radio"/>

A full range of options are available upon request

Specifications

 **MAX PAYLOAD**
20,000 kg

 **SPREAD WIDTH**
Urea 36m / SSP 50m

CAPACITY
14,000L

TARE WEIGHT
6,200kg

LOADING HEIGHT
3,000mm

UREA CAPACITY
11,000kg

LIME CAPACITY
18,000kg

BIN LENGTH
5,100mm

OVERALL LENGTH
7,900mm

BIN WIDTH
2,400mm

STANDARD WHEEL TRACK
2,400mm

CONVEYER WIDTH
750mm wide

OIL FLOW
140L/min

WARRANTY
12 months

Hansa provides all information in good faith, and reserves all rights to alter/change specifications without notice. Purchasers must conduct their own enquiries to ensure that the products are suitable for their own particular purposes as all information is provided as an approximation and are to be used as a guide only. Photographs may show aftermarket or optional equipment that is available at extra cost. Hansa Precision Equipment Pty Ltd. Copyright 2021. ABN: 74 604 073 350

139 Learmonth St, Alfredton VIC
sales@hansaequipment.com.au
hansaequipment.com.au

